

Page 1/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

- · Article number: 0781 120 1116, 0781 120 1117, 0781 120 1118, 0781 120 1022
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Application of the substance / the mixture Lubricating grease.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ANDREAS STIHL AG & Co.KG

Badstr. 115

D-71336 Waiblingen Tel: +49(0)7151-26-3237 Fax: +49(0)7151-26-8-3237 Email: info@stihl.com

Informing department:

Produktmanagement Forsttechnik

Tel: +49(0)7151-26-3237 Fax: +49(0)7151-26-83237

· 1.4 Emergency telephone number:

Emergency control center for poisoning cases Berlin +49 (0) 30 30 686 790 (German and English) Information for transport Tel.: +49-621-60-43333 Fax: 49-621-60-92664

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
 The product is not classified according to the CLP regulation.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

GB

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

- · Description: Mixture of base oils with additives and lithium soaps as thickener.
- · Dangerous components: Void
- · Additional information

Highly refined mineral oil (IP 346 DMSO < 3%)

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing Do not induce vomiting; instantly call for medical help.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

Extinguishing powder, foam or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire

Carbon monoxide (CO)

Nitrogen oxides (NOx)

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Avoid contact with the product.

· 6.2 Environmental precautions:

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders) and disposal in suitable containers.

(Contd. on page 3)

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 2)

· 6.4 Reference to other sections See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires:

Protect from heat.

The product forms flammable fumes when heated.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Storage between 0 and 55 °C.

Store under dry conditions.

Protect from heat and direct sunlight.

- · Storage class 11
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Oil resistant gloves

In case of longer or repeated contact with the skin: use protective cream for the skin surfaces coming into contact with the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC gloves

· Eye protection: Safety glasses recommended during refilling.

(Contd. on page 4)

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 3)

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
Colour: Brown

Odour: Type specific

· pH-value at 20°C: n.a.

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: >200°C

Drip point: 175°C (ASTM D 566)

• Flash point: >230°C (ASTM D 92)

· Ignition temperature: >300°C (DIN 51794)

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Vapour pressure at 20°C: <0.1 hPa

· Density at 20°C 0.9 g/cm³

· Solubility in / Miscibility with

Water: Insoluble

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic: Not applicable. kinematic: Not applicable.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Avoid contact with strong oxidizing agents.
- 10.6 Hazardous decomposition products:

Nitrogen oxides (NOx)

Sulphur oxides (SOx)

Carbon monoxide and carbon dioxide

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 4)

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability The product is not easily, but potentially biodegradable.
- · Other information:

Biodegradability is not probable due to the consistency as well as the low degree of water solubility of the product.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

The waste code numbers mentioned are recommendations based on the probable use of the product.

The product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

- Uncleaned packagings:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

(Contd. on page 6)

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 5)

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information	ion
· 14.1 UN-Number · ADR/RID/ADN, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR/RID/ADN, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Ann of Marpol and the IBC Code	nex II Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data specification sheet:

The safety data sheets were drawn up in cooperation with the Umweltkanzlei Dr.Rhein Beratungsund Prüfgesellschaft mbH, Phone: +49 5066 900990.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 7)

Printing date 09.08.2017 Version number 5 Revision: 09.08.2017

Trade name: STIHL Superlub FS

Getriebefett für Motorsensen und Freischneider Gear lubricant for brushcutters and clearing saws

(Contd. of page 6)

vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

GR.